



() mit unabhängiger Hinterachslenkung



DIN /ISO
EN 13000

m	7,8	10,7	13,6	19,5	25,3	28,4	31,2	m
3,0	15,0	15,0	15,0					3,0
3,5	15,0	15,0	15,0					3,5
4,0	15,0	15,0	15,0					4,0
4,5	15,0	15,0	15,0	15,0				4,5
5,0	15,0	15,0	15,0	15,0				5,0
6,0		15,0	15,0	14,5				6,0
7,0		15,0	15,0	13,6	11,9			7,0
8,0		14,1	14,3	12,5	11,0	9,8		8,0
9,0			12,6	11,6	10,2	9,1	8,3	9,0
10,0			10,5	10,3	9,5	8,6	7,8	10,0
12,0				7,5	7,6	7,6	6,8	12,0
14,0				6,2	5,8	5,8	5,8	14,0
16,0				5,0	4,5	4,8	4,6	16,0
18,0					4,0	3,9	3,7	18,0
20,0					3,4	3,2	2,9	20,0
22,0					2,9	2,6	2,3	22,0
24,0						2,1	1,9	24,0
26,0						1,8	1,5	26,0
28,0							1,2	28,0
0°	15,0	11,0	7,5	3,8	2,2	1,4	0,8	0°

- > 40° Arbeitsbereich – lange Absteckung Montagespitze
- 25–40° Arbeitsbereich – mittlere Absteckung Montagespitze
- < 25° Arbeitsbereich – kurze Absteckung Montagespitze
- 0° Arbeitsbereich – mittlere und kurze Absteckung Montagespitze



Gewicht für Hakenflasche und Anschlagmittel müssen zur Last addiert werden und werden bei Bedarf einsatzspezifisch genannt.